

Material Safety Data Sheet
May be used to comply with:
OSHA's Hazard Communication Standard
29 CFR 1910.1200. Standard must be:
consulted for specific requirements:

U.S. Department of Labor
Occupational Safety & Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY: **RAECO LEVEL-FLEX LATEX ADMIXTURE** Revised 1-10-2004

Section I

Manufacturer Name: Raeco, Inc.
Address: 915 S. Carstens Pl.
P.O. Box 80545
Seattle, Washington 98108
(206) 763-1335

Section II - Hazardous Ingredients/Identity Information

<u>Hazardous Components</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>Other Limits</u>
-----------------------------	-----------------	------------------	---------------------

Acrylic Polymer	Not Hazardous		
Residual Monomers	Not Hazardous		

Not a hazardous material as defined in title 29 CFR parts 1900 to 1910

Section III - Physical/Chemical Characteristics

Boiling Point:	212F
Specific Gravity (H ₂ O=1):	.98-1.04
Vapor Pressure (mm Hg):	17.5 mm Hg @ 20C
Melting Point:	NA
Vapor Density (AIR=1):	.624 @ 80F
Evaporation Rate (Butyl Acetate=1):	NA
Solubility in Water:	Emulsion
Appearance & Odor:	White Liquid with Slight Odor

Section IV - Fire & Explosion Hazard Data

Flash Point:	NA
Flammable Limits:	NA
Extinguishing Media:	NA

Special Fire Fighting Procedures: Water fog dried resin only. Wear positive pressure self-contained breathing apparatus.

Unusual Fire & Explosion Hazards: As latex, material's not combustible; however dried resin is combustible similar to wood. Burning dried resin emits dense black smoke.

Section V - Reactivity Data

Stability: Stable
Conditions to Avoid: NA
Incompatibility (Materials to Avoid): Materials that react violently with water
Hazardous Polymerization: Will not occur
Hazardous Decomposition or Byproducts: If dried film burns, it will produce carbon monoxide & hydrocarbons

Section VI - Health Hazard Data

Route(s) of Entry: Inhalation: Yes Skin: Yes Ingestion: No
Health Hazard (Acute or Chronic): Vapor or mist can cause headache, nausea & irritation of the nose, throat, lungs & skin under prolonged contact. Slight irritation to eyes.
Carcinogenicity: No NTP: No IARC Monographs: Yes OSHA Regulated: No
Signs & Symptoms of Exposure: Reddening of eyes & skin upon contact. Coughing upon inhalation of vapors.
Medical Conditions: Hypersensitive individuals may develop allergenic dermatitis
First Aid Procedures: Flush eyes with large amounts of water for at least 15 minutes, wash affected area with soap & water, see physician if irritation persists.

Section VII - Precautions for Safe Handling & Use

Steps to Take in Case Material is Released or Spilled: Floor will be slippery; use care to avoid falling. Contain spills with sand or earth. Transfer to containers for recovery or disposal.
Waste Disposal Method: Coagulate the emulsion by stepwise addition of ferric chloride & lime. Remove the supernatant liquid & flush to chemical sewer. Landfill/incinerate.
Precautions to Be Taken in Handling & Storing: Keep from freezing, keep temperatures below 100C.

Section VIII - Control Measures

Respiratory Protection: Not required with good ventilation. OSHA approved respirator
Ventilation: Local Exhaust: Yes Mechanical: NA Other: No
Protective Gloves: Impervious Eye Protection: Splash goggles
Other Protective Clothing or Equipment: None
Work/Hygienic Practices: Normal care & cleanliness will prevent adverse health effects.