



QUALITY AMERICAN SPECIALTY CEMENT MANUFACTURER
FOR OVER 100 YEARS

Architectural Product Line Card

www.raecoinc.com

Section 03 5400- Cementitious Trowel Grade Underlayments

- **Glide:** A Calcium aluminate based, ultra-smooth finishing, polymer modified patching compound, ideally suited for skimming floors and wall up to ½" depth. Glide is the fastest setting floor patch in the U.S. and is ready for flooring or painting in 15 minutes. Interior or Exterior. Use above grade only.
- **Feather Spread:** A REAL Portland based, single component, fast-setting, smooth textured polymer cement based compound for patching and smoothing floors, walls, and overhead surfaces. Interior or Exterior.
- **Buttercoat RPS:** A REAL Portland based, multi-purpose, single-component, polymer modified patching compound that can go from a featheredge to 2" depth. (Longer pot-life and working time than Glide.) Interior or Exterior.
- **R-100:** A REAL Portland-based, single component, trowel applied, sandable underlayment for smoothing and leveling floors. Interior or exterior.
- **R-25 Underlayment:** Two-component, trowel applied, sandable underlayment for smoothing & leveling irregular concrete floors.
- **Buttercoat:** A thin trowel-applied topping with extremely high flexural strength and good abrasion resistance. Unlike un-sanded "micro-toppings", this topping contains a fine silica aggregate and is suitable for high foot traffic and vehicular traffic. Available in gray or white. Two-component. Interior or exterior.
- **Level-Flex Underlayment:** Two-component trowel applied flexible mortar for leveling subfloors subject to flex (wood, metal, etc.) Interior or Exterior.

Section 03 5400: Cementitious Self-Leveling Underlayments

- **S.L.U.** (Self-Leveling Underlayment): A REAL Portland-based, single component, polymer-modified leveling cement for interior floors. May be installed from 1/8" inch up to 5" inches with the addition of pea gravel. Takes less labor time for installation. Ready for most floor covering in 24 hours. Interior or Exterior.
- **SLU-Fast Set:** The most flowable self-leveling product made by RAECO. A single component, polymer-modified self-leveling product, which rapidly hydrates over 90% of its mix water. Made with a ternary blend of calcium aluminate and Portland cements, it reaches over 2000 psi in 24 hours curing. May be installed from 1/8" inch up to 5" inches with the addition of pea gravel. Ready for most floor coverings in 12 hours. Interior only.
- **Ultra-Light SLU:** A very flowable self-leveling product that utilizes recycled glass beads to product an underlayment that is 40% lighter than standard self-leveling cement-based underlayments (72 lbs/cubic foot). High Strength, fast-setting underlayment is ready for flooring in 6-8 hours. Post-Consumer recycled content is 23% by weight, over 50% by volume. Interior only.

Section 03 9910 Concrete Patch- Vertical and Overhead Patches (Alternate Section 03 9925 - Decorative Concrete Resurfacing-Vertical)

- **Glide:** A Calcium aluminate based, ultra-smooth finishing, polymer modified patching compound, ideally suited for skimming floors and wall up to ½" depth. Ready for flooring or painting in 15 minutes. Over 5200 PSI in 7-days. Interior or Exterior, above grade only. Must be sealed or painted.
- **SkimWall:** A REAL Portland cement based, polymer-modified skimming compound, with four Shades of Gray to match new concrete colors. Interior or exterior.
- **Sack & Patch:** Polymer fortified, fast setting sacking/patching mix for walls or floors. Interior or exterior.



QUALITY AMERICAN SPECIALTY CEMENT MANUFACTURER
FOR OVER 100 YEARS

Architectural Product Line Card

www.raecoinc.com

Section 03 9920: Concrete Patching-Trowel Grade Toppings & Resurfacers

- **R-50 Overlayment:** Two-component, trowel applied concrete topping for leveling, sloping, or repair of floors, sidewalks, exterior slabs, parking decks. May be smooth trowelled or broom finished. Interior or Exterior.
- **R-50 Fiber Reinforced Topping:** For challenging substrates with expected thermal movement and deflection. Install from 1/8" to any depth with proper aggregate (use aggregate for depths greater than 3/4".) May be used as an unbonded topping slab at 2" depth. Interior or Exterior.
- **Buttercoat:** Smooth, fine textured powder, two-component topping blended with any RAECO Latex Additive, for smoothing rough concrete or rough underlayment jobs. May be smooth-trowelled or broom-finished. Interior or exterior.
- **Quick-Fix:** Single component fast-setting concrete repair mortar for horizontal, vertical, or overhead jobs including those to be covered with epoxy coatings. Interior or exterior.

Section 09 6230: Decorative Concrete Toppings

- **SLT-HS:** A REAL Portland-based, self-leveling topping that provides a durable wear surface. Available in gray or white. Desirable for decorative floors utilizing stains or integral colored pigments. Interior or exterior.
- **Eco Pour Self-Leveling Topping:** World first recycled self-leveling topping system, utilizing 30% Post-Consumer sands from recycled concrete. Over 6000 psi compressive strength
- **Buttercoat:** A thin trowel-applied topping with extremely high flexural strength and good abrasion resistance. Unlike un-sanded "micro-toppings", this topping contains a fine silica aggregate and is suitable for high foot traffic and vehicular traffic. Available in gray or white. Two-component. Interior or exterior.